

## **Endoscope Storage Cabinet with Drying System**









## **COMPLIANT WITH ST91:2021**

- Endoscopes hang freely and don't touch each other, the back wall, or the floor
- Bright LED lights illuminate inventory
- 24/7 HEPA maximum airflow positive pressure
- No floor level vents to draw in dust and dirt.
- · Removable drip tray, easy to clean

- Earthquake compliant
- Free standing
- Space saving technology small footprint
- Joint Commission inspection friendly
- Meets or exceeds all current standards
  ANSI®, AAMI® ST91:2021, AORN®, and SGNA®
  compliant
- Modular design is upgradeable to meet future guidelines



Clinical Choice, LLC 5574 Garden Village Way Suite D400 Greensboro, NC 27410 Phone: 877.572.9985 Fax: 877.572.9986 www.clinicalchoice.com





## Got Compliance? We've Got You Covered.

Guidelines	ScopeVAULT™	SGNA®	AORN®	AAMI®
Clean, well-ventilated and dust free	⊗	⊗	<b>⊘</b>	<b>⊘</b>
Endoscopes should not touch each other (hang freely)	$\otimes$	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Endoscopes should not touch the bottom of the cabinet	$\otimes$	-	<b>⊘</b>	<b>⊘</b>
Endoscopes should not be coiled*	$\otimes$	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Cabinets should have venting that allows air circulation around the endoscopes	$\otimes$	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Sufficient space between and around scopes	$\otimes$	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Cabinets should be made of a material that can be disinfected	$\otimes$	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Endoscopes should hang in a vertical position*	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>
Area temperature and humidity should be monitored	⊗	-	-	<b>⊘</b>
Flexible and semi-rigid endoscopes should be stored in a closed cabinet	<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>

## \*Per OEM IFU







Maximum Airflow



Small Footprint



Modular Design



Infection Control

	ScopeVAULT Cabinet Specifications
Model ID: SV-DRI	ScopeVault Endoscope Storage Cabinet with Drying System
Specifications	250+/- pounds   91.25"H x 30"W x 20"D
VOLTAGE	120V 20A Circuit